















Wall-mounted











M series LED controller is compatible with 8 kinds remotes of different function (patent technology) . which means using one receiver could experience single color/CT dimming, RGB/RGBW adjustment to meet customers' different lighting requirements. With the RF remote, speed/brightness adjustment. customise color and lighting changing modes selection could all be achieved

1

#### Remote(RGB):

Model: M3/M6/M7

Working Voltage: 3V DC(battery CR2032)

• Working Frequency: 433.92MHz

• Remote Distance: 40~50m Working Temp.: -30°C~55°C

• Weight(N.W.): 42g

#### CV Receiver (RGB):

Model: M4-5A

• Input Voltage: 5~24V DC


• Max Current Load: 6A×3CH Max 18A


Max Output Power: 90W/216W/432W(5V/12V/24V)


• Working Temp.: -30°C~55°C

Weight(N.W.): 125g

### 2. Product Size:







### 3. The Learning ID Method of Remote Control:

Remote control has been matched with the receiver before leaving factory, if deleted accidentally, you can learn ID as follow.

Learning ID: Short press ID learning button on the M4-5A receiver, the running light is on, then press any key on the M3/M6/M7 remote control, the running light flashes several times, activated.

Cancel ID: Long press ID learning button on the M4-5A receiver for 5 seconds.

Attn: One receiver can be matched with max 10 same or different kinds remote control.

#### 4. Operating Instruction for Receiver:



2



## LTECH


### 5. Operating Instruction for Remote Control:


**Sleep Mode:** the M3 remote goes on a standby mode to save power when not in use for 30s. press any key to continue.



#### M3 Changing Mode Table

No.	Mode	No.	Mode
1	Static Red	7	Static White
2	Static Green	8	RGB Skipping
3	Static Blue	9	7 Colors Skipping
4	Static Yellow	10	RGB Color Smooth
5	Static Purple	11	Full-color Smooth
6	Static Cyan		





# 6. Wiring Diagram:

