


BFRGBWW060

LED FLEXIBLE STRIPS

SMD5050 60-LED/m 24V DC



This product is based on our most popular High Quality SAN'AN 5050 SMD LED (5 chips in 1 led). This version offers an excellent combination of high light output with a strong colour to provide outstanding results. Available in all colours to cover most requirements. Supplied in 24V DC as standard for more accurate cut lengths. Bin control for led color to ensure consistent color throughout all of your orders.

PRODUCT FEATURE & BENEFITS

- ◆ Always using double-layer FPCB, mounted with high quality led Chips
- ◆ Low power requirement & Energy Efficient
- ◆ High color rendering RA > 80
- ◆ High-performance FPCB & LED for extremely long life
- ◆ Available in IP20, IP54, IP62, IP65 rating
- ◆ Great design freedom thanks to flexibility and cuttability of module
- ◆ Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back

BFRGBWW060

LED FLEXIBLE STRIPS

SMD5050 60-LED/m 24V DC

PRODUCT CODE

BF	RGBWW	060	L2	80	S	12	R	11	20
RGBWW - SMD5050 LED	060 - 60 LEDs/m	L2 - 24V DC	80 - RA>80	S - SAN'AN LED	12 - PCB Width 12mm	2 - PCB 2OZ 3 - PCB 3OZ 4 - PCB 4OZ R - PCB 2OZ (Rolled Copper)	11 - RGBWW	20 - IP20 54 - IP54 62 - IP62 65 - IP65	

TECHNICAL DATA

LED Brand	SAN'AN LED
Normal Voltage	24V DC
Normal Current per Meter	1.0A/m
Rated Wattage per Meter	24W/m
Type of Current	Direct Current / Constant Voltage
Light Color	See Form 1
Luminous Flux per Meter	2040 lm
Luminous Efficacy	85 lm/W
Color Rendering Index / RA	RA > 80
Length per Smallest Cutting Unit	100 mm (24V DC)
LED Number per Smallest Cutting Unit	6 LEDs (24V DC)
Length per roll for package	5 meters / 10 meters / 20 meters / 30 meters
Width of Printed Circuit Board	12 mm
Color of Printed Circuit Board	White / Black
Thickness of Printed Circuit Board	2 OZ (Rolled Copper)
Double Side Adhesive Tape	3M 300LSE
Temperature Range in Operation	-20°C ... 70°C
Temperature Range at Storage	-20°C ... 50°C
Dimmable	Yes
Type of Protection	IP20 / IP54 / IP62 / IP65
Life Span	> 50000 Hours

* Testing environment temperature: 25±2°C

* The actual data of each single product may differ from above typical data which are subject to change without prior notice.

BFRGBWW060

LED FLEXIBLE STRIPS



SMD5050 60-LED/m 24V DC

LIGHT COLOR

Form 1

LED Color	OSRAM LED	EPISTAR LED	SAN'AN LED
White Color 7500K (75)			
White Color 6500K (65)			
White Color 5700K (57)			
White Color 5000K (50)			
White Color 4000K (40)			
White Color 3000K (30)			
White Color 2700K (27)			
White Color 2400K (24)			
White Color 2000K (20)			
Red Color (RE)			
Green Color (GR)			
Blue Color (BL)			
Yellow Color (YE)			
Pink Color (PI)			
Purple Color (PU)			
RGBWW(6500K+RGB+3000K)(11)			✓

PRODUCT START/END OPTIONS



◆ The standard products are with soldered wire on both start and end section. For other options, please let us know before placing orders.


BFRGBWW060

LED FLEXIBLE STRIPS

SMD5050 60-LED/m 24V DC

CONNECTIONS

LED Strip Lighting can be installed any number of ways, but there are one way to go about it. Check out the configuration below:




BFRGBWW060

LED FLEXIBLE STRIPS

SMD5050 60-LED/m 24V DC

INSTALLATION INSTRUCTIONS

1. The mounting surface must be clean, dry and free from dust or grease.
2. Release the LED strip from the package and unreel.
3. Measure and cut the LED strip to the required length (only cut at the cut marks with power OFF).
4. Remove the 3M self-adhesive backing tape from the strip gradually during installation.
DO NOT remove it all at once to avoid the strip becoming entangled and sticking to itself.
5. Stick the LED strip to the mounting surface by pressing on the strip in between components only.
DO NOT press on the LEDs or other components on the strip.
6. You can use optional mounting clips to secure the strips at intervals.
7. Once the strip is affixed, it is then ready to be wired.

 **CAUTION** - Twisting, pressing on LEDs, over-bending the strip, cutting at non-cut points, incorrectly powering the strip or exposing a standard strip (IP20) to water, particles or direct sunlight will invalidate the warranty.

SAFTY

1. Installation must be in accordance with local and national electrical code regulations.
2. To ensure safety and correct installation, our strips are intended to be installed by a licensed electrician.
3. Only install with a Constant Voltage LED driver.
4. Each maximum run requires a dedicated power feed from the driver.
DO NOT extend beyond the recommended maximum run length.
5. Make sure the appropriate gauge wire is installed between driver, LEDs, and any dimmers. When choosing wire, calculate voltage drop, maximum amperage rating, and the location ratings on the wire. Improper wire selection and installation could overheat wires and cause fire.
7. **DO NOT** modify product beyond instructions or warranty will be void.



Questions? Please contact us via info@lip-technik.com